

NAME

PKCS7_encrypt_ex, PKCS7_encrypt - create a PKCS#7 envelopedData structure

SYNOPSIS

```
#include <openssl/pkcs7.h>
```

```
PKCS7 *PKCS7_encrypt_ex(STACK_OF(X509) *certs, BIO *in,  
                        const EVP_CIPHER *cipher, int flags,  
                        OSSL_LIB_CTX *libctx, const char *propq);  
PKCS7 *PKCS7_encrypt(STACK_OF(X509) *certs, BIO *in, const EVP_CIPHER *cipher,  
                    int flags);
```

DESCRIPTION

PKCS7_encrypt_ex() creates and returns a PKCS#7 envelopedData structure. *certs* is a list of recipient certificates. *in* is the content to be encrypted. *cipher* is the symmetric cipher to use. *flags* is an optional set of flags. The library context *libctx* and the property query *propq* are used when retrieving algorithms from providers.

Only RSA keys are supported in PKCS#7 and envelopedData so the recipient certificates supplied to this function must all contain RSA public keys, though they do not have to be signed using the RSA algorithm.

EVP_des_ede3_cbc() (triple DES) is the algorithm of choice for S/MIME use because most clients will support it.

Some old "export grade" clients may only support weak encryption using 40 or 64 bit RC2. These can be used by passing **EVP_rc2_40_cbc()** and **EVP_rc2_64_cbc()** respectively.

The algorithm passed in the **cipher** parameter must support ASN1 encoding of its parameters.

Many browsers implement a "sign and encrypt" option which is simply an S/MIME envelopedData containing an S/MIME signed message. This can be readily produced by storing the S/MIME signed message in a memory BIO and passing it to **PKCS7_encrypt()**.

The following flags can be passed in the **flags** parameter.

If the **PKCS7_TEXT** flag is set MIME headers for type **text/plain** are prepended to the data.

Normally the supplied content is translated into MIME canonical format (as required by the S/MIME specifications) if **PKCS7_BINARY** is set no translation occurs. This option should be used if the

supplied data is in binary format otherwise the translation will corrupt it. If **PKCS7_BINARY** is set then **PKCS7_TEXT** is ignored.

If the **PKCS7_STREAM** flag is set a partial **PKCS7** structure is output suitable for streaming I/O: no data is read from the BIO in.

If the flag **PKCS7_STREAM** is set the returned **PKCS7** structure is **not** complete and outputting its contents via a function that does not properly finalize the **PKCS7** structure will give unpredictable results.

Several functions including **SMIME_write_PKCS7()**, **i2d_PKCS7_bio_stream()**, **PEM_write_bio_PKCS7_stream()** finalize the structure. Alternatively finalization can be performed by obtaining the streaming ASN1 **BIO** directly using **BIO_new_PKCS7()**.

PKCS7_encrypt() is similar to **PKCS7_encrypt_ex()** but uses default values of NULL for the library context *libctx* and the property query *propq*.

RETURN VALUES

PKCS7_encrypt_ex() and **PKCS7_encrypt()** return either a **PKCS7** structure or NULL if an error occurred. The error can be obtained from **ERR_get_error(3)**.

SEE ALSO

ERR_get_error(3), **PKCS7_decrypt(3)**

HISTORY

The function **PKCS7_encrypt_ex()** was added in OpenSSL 3.0.

The **PKCS7_STREAM** flag was added in OpenSSL 1.0.0.

COPYRIGHT

Copyright 2002-2020 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.