

**NAME**

SSL\_CONF\_CTX\_set\_ssl\_ctx, SSL\_CONF\_CTX\_set\_ssl - set context to configure

**SYNOPSIS**

```
#include <openssl/ssl.h>
```

```
void SSL_CONF_CTX_set_ssl_ctx(SSL_CONF_CTX *cctx, SSL_CTX *ctx);
```

```
void SSL_CONF_CTX_set_ssl(SSL_CONF_CTX *cctx, SSL *ssl);
```

**DESCRIPTION**

**SSL\_CONF\_CTX\_set\_ssl\_ctx()** sets the context associated with **cctx** to the **SSL\_CTX** structure **ctx**. Any previous **SSL** or **SSL\_CTX** associated with **cctx** is cleared. Subsequent calls to **SSL\_CONF\_cmd()** will be sent to **ctx**.

**SSL\_CONF\_CTX\_set\_ssl()** sets the context associated with **cctx** to the **SSL** structure **ssl**. Any previous **SSL** or **SSL\_CTX** associated with **cctx** is cleared. Subsequent calls to **SSL\_CONF\_cmd()** will be sent to **ssl**.

**NOTES**

The context need not be set or it can be set to **NULL** in which case only syntax checking of commands is performed, where possible.

**RETURN VALUES**

**SSL\_CONF\_CTX\_set\_ssl\_ctx()** and **SSL\_CTX\_set\_ssl()** do not return a value.

**SEE ALSO**

**ssl(7)**, **SSL\_CONF\_CTX\_new(3)**, **SSL\_CONF\_CTX\_set\_flags(3)**, **SSL\_CONF\_CTX\_set1\_prefix(3)**, **SSL\_CONF\_cmd(3)**, **SSL\_CONF\_cmd\_argv(3)**

**HISTORY**

These functions were added in OpenSSL 1.0.2.

**COPYRIGHT**

Copyright 2012-2016 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.