### **NAME**

```
SSL_set_fd, SSL_set_rfd, SSL_set_wfd - connect the SSL object with a file descriptor
```

## **SYNOPSIS**

```
#include <openssl/ssl.h>
int SSL_set_fd(SSL *ssl, int fd);
int SSL_set_rfd(SSL *ssl, int fd);
int SSL_set_wfd(SSL *ssl, int fd);
```

## DESCRIPTION

**SSL\_set\_fd()** sets the file descriptor **fd** as the input/output facility for the TLS/SSL (encrypted) side of **ssl. fd** will typically be the socket file descriptor of a network connection.

When performing the operation, a **socket BIO** is automatically created to interface between the **ssl** and **fd**. The BIO and hence the SSL engine inherit the behaviour of **fd**. If **fd** is nonblocking, the **ssl** will also have nonblocking behaviour.

If there was already a BIO connected to **ssl**, **BIO\_free()** will be called (for both the reading and writing side, if different).

**SSL\_set\_rfd()** and **SSL\_set\_wfd()** perform the respective action, but only for the read channel or the write channel, which can be set independently.

# **RETURN VALUES**

The following return values can occur:

- 0 The operation failed. Check the error stack to find out why.
- 1 The operation succeeded.

### **NOTES**

On Windows, a socket handle is a 64-bit data type (UINT\_PTR), which leads to a compiler warning (conversion from 'SOCKET' to 'int', possible loss of data) when passing the socket handle to SSL\_set\_\*fd(). For the time being, this warning can safely be ignored, because although the Microsoft documentation claims that the upper limit is INVALID\_SOCKET-1 (2^64 - 2), in practice the current socket() implementation returns an index into the kernel handle table, the size of which is limited to 2^24.

## **SEE ALSO**

 $\mathbf{SSL\_get\_fd}(3), \mathbf{SSL\_set\_bio}(3), \mathbf{SSL\_connect}(3), \mathbf{SSL\_accept}(3), \mathbf{SSL\_shutdown}(3), \mathbf{ssl}(7), \mathbf{bio}(7)$ 

# **COPYRIGHT**

Copyright 2000-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <a href="https://www.openssl.org/source/license.html">https://www.openssl.org/source/license.html</a>>.

3.0.11 2023-09-19 SSL\_SET\_FD(3ossl)