

NAME

XChangeSaveSet, XAddToSaveSet, XRemoveFromSaveSet - change a client's save set

SYNTAX

```
int XChangeSaveSet(Display *display, Window w, int change_mode);
```

```
int XAddToSaveSet(Display *display, Window w);
```

```
int XRemoveFromSaveSet(Display *display, Window w);
```

ARGUMENTS

change_mode Specifies the mode. You can pass **SetModeInsert** or **SetModeDelete**.

display Specifies the connection to the X server.

w Specifies the window that you want to add or delete from the client's save-set.

DESCRIPTION

Depending on the specified mode, **XChangeSaveSet** either inserts or deletes the specified window from the client's save-set. The specified window must have been created by some other client, or a **BadMatch** error results.

XChangeSaveSet can generate **BadMatch**, **BadValue**, and **BadWindow** errors.

The **XAddToSaveSet** function adds the specified window to the client's save-set. The specified window must have been created by some other client, or a **BadMatch** error results.

XAddToSaveSet can generate **BadMatch** and **BadWindow** errors.

The **XRemoveFromSaveSet** function removes the specified window from the client's save-set. The specified window must have been created by some other client, or a **BadMatch** error results.

XRemoveFromSaveSet can generate **BadMatch** and **BadWindow** errors.

DIAGNOSTICS

BadMatch Some argument or pair of arguments has the correct type and range but fails to match in some other way required by the request.

BadValue Some numeric value falls outside the range of values accepted by the request. Unless a specific range is specified for an argument, the full range defined by the argument's

type is accepted. Any argument defined as a set of alternatives can generate this error.

BadWindow A value for a Window argument does not name a defined Window.

SEE ALSO

XReparentWindow(3)

Xlib - C Language X Interface