

NAME

XStoreBytes, XStoreBuffer, XFetchBytes, XFetchBuffer, XRotateBuffers - manipulate cut and paste buffers

SYNTAX

```
int XStoreBytes(Display *display, _Xconst char *bytes, int nbytes);
```

```
int XStoreBuffer(Display *display, _Xconst char *bytes, int nbytes, int buffer);
```

```
char *XFetchBytes(Display *display, int *nbytes_return);
```

```
char *XFetchBuffer(Display *display, int *nbytes_return, int buffer);
```

```
int XRotateBuffers(Display *display, int rotate);
```

ARGUMENTS

buffer Specifies the buffer in which you want to store the bytes or from which you want the stored data returned.

bytes Specifies the bytes, which are not necessarily ASCII or null-terminated.

display Specifies the connection to the X server.

nbytes Specifies the number of bytes to be stored.

nbytes_return Returns the number of bytes in the buffer.

rotate Specifies how much to rotate the cut buffers.

DESCRIPTION

The data can have embedded null characters and need not be null-terminated. The cut buffer's contents can be retrieved later by any client calling **XFetchBytes**.

XStoreBytes can generate a **BadAlloc** error.

If an invalid buffer is specified, the call has no effect. The data can have embedded null characters and need not be null-terminated.

XStoreBuffer can generate a **BadAlloc** error.

The **XFetchBytes** function returns the number of bytes in the `nbytes_return` argument, if the buffer contains data. Otherwise, the function returns NULL and sets `nbytes` to 0. The appropriate amount of storage is allocated and the pointer returned. The client must free this storage when finished with it by calling **XFree**.

The **XFetchBuffer** function returns zero to the `nbytes_return` argument if there is no data in the buffer or if an invalid buffer is specified.

XFetchBuffer can generate a **BadValue** error.

The **XRotateBuffers** function rotates the cut buffers, such that buffer 0 becomes buffer `n`, buffer 1 becomes $n + 1 \bmod 8$, and so on. This cut buffer numbering is global to the display. Note that **XRotateBuffers** generates **BadMatch** errors if any of the eight buffers have not been created.

XRotateBuffers can generate a **BadMatch** error.

DIAGNOSTICS

- | | |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BadAlloc | The server failed to allocate the requested resource or server memory. |
| BadAtom | A value for an Atom argument does not name a defined Atom. |
| BadMatch | Some argument or pair of arguments has the correct type and range but fails to match in some other way required by the request. |
| BadValue | Some numeric value falls outside the range of values accepted by the request. Unless a specific range is specified for an argument, the full range defined by the argument's type is accepted. Any argument defined as a set of alternatives can generate this error. |

SEE ALSO

XFree(3)

Xlib - C Language X Interface