

NAME

Xinerama - API for Xinerama extension to X11 Protocol

SYNOPSIS

```
#include <X11/extensions/Xinerama.h>
```

```
Bool XineramaQueryExtension (Display *dpy,  
                             int *event_base_return, int *error_base_return);
```

```
Status XineramaQueryVersion (Display *dpy,  
                              int *major_version_return,  
                              int *minor_version_return);
```

```
Bool XineramaIsActive (Display *dpy);
```

```
XineramaScreenInfo * XineramaQueryScreens (Display *dpy,  
                                           int *number);
```

ARGUMENTS

display Specifies the connection to the X server.

event_base_return
Specifies the return location for the assigned base event code

error_base_return
Specifies the return location for the assigned base error code

major_version_return
Returns the major version supported by the server

minor_version_return
Returns the minor version supported by the server

number Returns the number of entries in the returned XineramaScreenInfo array.

DESCRIPTION

Xinerama is a simple library designed to interface the Xinerama Extension for retrieving information about physical output devices which may be combined into a single logical X screen.

FUNCTIONS

XineramaQueryExtension()

The `XineramaQueryExtension` function queries the Xserver to determine the availability of the Xinerama Extension. If the extension is available, the return value is `True`, and `event_base_return` and `error_base_return` are set to the base event number and base error number for the extension, respectively. Otherwise, the return value is `False`, and the values of `event_base_return` and `error_base_return` are undefined.

XineramaQueryVersion()

The `XineramaQueryVersion` function returns the version of the Xinerama extension implemented by the Xserver. The version is returned in `major_version_return` and `minor_version_return`. The major version will be incremented for protocol incompatible changes, and the minor version will be incremented for small, upwardly compatible changes.

If the Xinerama library is compatible with the version returned by the server, it returns nonzero. If the server does not support the XINERAMA extension, or if there was an error during communications with the server, or if the server and library protocol versions are incompatible, it returns zero.

XineramaIsActive()

The `XineramaIsActive` function returns a Boolean operator used to determine if Xinerama is activated on the screen. Returns `True` for active and `False` for not active.

XineramaQueryScreens()

The `XineramaQueryScreens()` function returns info about each individual output device within the Xinerama Screen. The integer pointed to by the *number* argument is updated to the number of output devices listed in the returned array of `XineramaScreenInfo` structures. `XineramaQueryScreens()` returns `NULL` and sets *number* to 0 if Xinerama is not active.

The pointer returned should be released with `XFree(3)` when no longer needed.

NOTE

The original API provided for interacting with the XINERAMA extension used function names

beginning with *XPanoramiX*. That API is now deprecated and this API should be used instead in new software.