

**NAME**

XkbRefreshKeyboardMapping - Update the keyboard description that is internal to the X library

**SYNOPSIS**

**Status** XkbRefreshKeyboardMapping (XkbMapNotifyEvent \**event*);

**ARGUMENTS**

*event*

event initiating remapping

**DESCRIPTION**

*XkbRefreshKeyboardMapping* is the Xkb equivalent of the core *XRefreshKeyboardMapping* function. It requests that the X server send the current key mapping information to this client. A client usually invokes *XkbRefreshKeyboardMapping* after receiving an XkbMapNotify event.

*XkbRefreshKeyboardMapping* returns Success if it succeeds and BadMatch if the event is not an Xkb event.

The XkbMapNotify event can be generated when some client calls *XkbSetMap*, *XkbChangeMap*, *XkbGetKeyboardByName*, or any of the standard X library functions that change the keyboard mapping or modifier mapping.

**RETURN VALUES**

Success	The <i>XkbRefreshKeyboardMapping</i> function returns Success when the request that the X server send the current key mapping information to this client is successful.
---------	---

**DIAGNOSTICS**

<b>BadMatch</b>	A compatible version of Xkb was not available in the server or an argument has correct type and range, but is otherwise invalid
-----------------	---

**SEE ALSO**

**XkbChangeMap(3), XkbGetKeyboardByName(3), XkbSetMap(3), XRefreshKeyboardMapping(3)**