

NAME

auditdistd - Audit trail files distribution daemon

SYNOPSIS

auditdistd [-dFhl] [-c *config*] [-P *pidfile*]

DESCRIPTION

The **auditdistd** daemon is responsible for distributing audit trail files over a TCP/IP network in a secure and reliable way.

The **auditdistd** daemon can be started with the following command line arguments:

- c *config*** Specify an alternative location of the configuration file. The default location is */etc/security/auditdistd.conf*. Note: the configuration file may contain passwords. Care should be taken to configure proper permissions on this file (eg. 0600).
- d** Print or log debugging information. This option can be specified multiple times to raise the verbosity level.
- F** Start the **auditdistd** daemon in the foreground. By default **auditdistd** starts in the background.
- h** Print the **auditdistd** usage message.
- l** Start in a launchd-friendly mode, ie. do not use `daemon(3)`.
- P *pidfile*** Specify an alternative location of a file where main process PID will be stored. The default location is */var/run/auditdistd.pid*.

FILES

/etc/security/auditdistd.conf The configuration file for **auditdistd**.

/var/run/auditdistd.pid The default location of the **auditdistd** PID file.

EXIT STATUS

Exit status is 0 on success, or one of the values described in `sysexits(3)` on failure.

SEE ALSO

`sysexits(3)`, `audit(4)`, `auditdistd.conf(5)`, `auditd(8)`

AUTHORS

The **auditdistd** was developed by Pawel Jakub Dawidek <pawel@dawidek.net> under sponsorship of the FreeBSD Foundation.