

NAME

fribidi_get_par_embedding_levels - get bidi embedding levels of a paragraph

SYNOPSIS

```
#include <fribidi.h>
```

```
FriBidiLevel fribidi_get_par_embedding_levels
(
    const FriBidiCharType *bidi_types,
    const FriBidiStrIndex len,
    FriBidiParType *pbase_dir,
    FriBidiLevel *embedding_levels
);
```

PARAMETERS

const FriBidiCharType *bidi_types

Input list of bidi types as returned by fribidi_get_bidi_types().

Since there are 23 possible values for a **const FriBidiCharType**, they are not all listed here.

const FriBidiStrIndex len

Input string length of the paragraph.

FriBidiParType *pbase_dir

Requested and resolved paragraph base direction.

Possible values for a **FriBidiParType** are as follows:

FRIBIDI_PAR_LTR	Left-To-Right paragraph.
FRIBIDI_PAR_RTL	Right-To-Left paragraph.
FRIBIDI_PAR_ON	DirectiOn-Neutral paragraph.
FRIBIDI_PAR_WLTR	Weak Left To Right paragraph.
FRIBIDI_PAR_WRTL	Weak Right To Left paragraph.

FriBidiLevel *embedding_levels

Output list of embedding levels.

DESCRIPTION

Deprecated interface to fribidi_get_par_embedding_levels_ex(). Refer to it for documentation.

SEE ALSO

fribidi_shape_arabic(3), fribidi_get_par_direction(3), fribidi_get_par_embedding_levels_ex(3),
fribidi_reorder_line(3), fribidi_get_bidi_type(3), fribidi_get_bidi_types(3),
fribidi_get_bidi_type_name(3), fribidi_debug_status(3), fribidi_set_debug(3),
fribidi_charset_to_unicode(3), fribidi_unicode_to_charset(3), fribidi_parse_charset(3),
fribidi_mirroring_status(3), fribidi_set_mirroring(3), fribidi_reorder_nsm_status(3),
fribidi_set_reordered_nsm(3), fribidi_log2vis_get_embedding_levels(3), fribidi_get_type(3),
fribidi_get_type_internal(3), fribidi_join_arabic(3), fribidi_get_joining_type(3),
fribidi_get_joining_types(3), fribidi_get_joining_type_name(3), fribidi_get_mirror_char(3),
fribidi_shape_mirroring(3), fribidi_get_bracket(3), fribidi_get_bracket_types(3), fribidi_shape(3),
fribidi_remove_bidi_marks(3), fribidi_log2vis(3)