

NAME

gnutls_certificate_get_trust_list - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
void gnutls_certificate_get_trust_list(gnutls_certificate_credentials_t res, gnutls_x509_trust_list_t *  
tlist);
```

ARGUMENTS

gnutls_certificate_credentials_t res

is a **gnutls_certificate_credentials_t** type.

gnutls_x509_trust_list_t * tlist

Location where to store the trust list.

DESCRIPTION

Obtains the list of trusted certificates stored in *res* and writes a pointer to it to the location *tlist*. The pointer will point to memory internal to *res*, and must not be deinitialized. It will be automatically deallocated when the *res* structure is deinitialized.

SINCE

3.4.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>