

NAME

gnutls_certificate_set_x509_crl - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_certificate_set_x509_crl(gnutls_certificate_credentials_t res, gnutls_x509_crl_t *crl_list, int crl_list_size);
```

ARGUMENTS

gnutls_certificate_credentials_t res
is a **gnutls_certificate_credentials_t** type.

gnutls_x509_crl_t *crl_list
is a list of trusted CRLs. They should have been verified before.

int crl_list_size
holds the size of the crl_list

DESCRIPTION

This function adds the trusted CRLs in order to verify client or server certificates. In case of a client this is not required to be called if the certificates are not verified using **gnutls_certificate_verify_peers2()**. This function may be called multiple times.

RETURNS

number of CRLs processed, or a negative error code on error.

SINCE

2.4.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>