

gnutls_certificate_set_x509_system_trust(3) gnutls gnutls_certificate_set_x509_system_trust(3)

NAME

gnutls_certificate_set_x509_system_trust - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_certificate_set_x509_system_trust(gnutls_certificate_credentials_t cred);
```

ARGUMENTS

gnutls_certificate_credentials_t cred
is a **gnutls_certificate_credentials_t** type.

DESCRIPTION

This function adds the system's default trusted CAs in order to verify client or server certificates.

In the case the system is currently unsupported **GNUTLS_E_UNIMPLEMENTED_FEATURE** is returned.

RETURNS

the number of certificates processed or a negative error code on error.

SINCE

3.0.20

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>