

NAME

gnutls_db_set_retrieve_function - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_db_set_retrieve_function(gnutls_session_t session, gnutls_db_retr_func retr_func);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

gnutls_db_retr_func retr_func

is the function.

DESCRIPTION

Sets the function that will be used to retrieve data from the resumed sessions database. This function must return a **gnutls_datum_t** containing the data on success, or a **gnutls_datum_t** containing null and 0 on failure.

The datum's data must be allocated using the function **gnutls_malloc()**.

The first argument to *retr_func* will be null unless **gnutls_db_set_ptr()** has been called.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>