

NAME

gnutls_ocsp_resp_get_response - API function

SYNOPSIS

```
#include <gnutls/ocsp.h>
```

```
int gnutls_ocsp_resp_get_response(gnutls_ocsp_resp_const_t resp, gnutls_datum_t *  
response_type_oid, gnutls_datum_t * response);
```

ARGUMENTS

gnutls_ocsp_resp_const_t resp

should contain a **gnutls_ocsp_resp_t** type

gnutls_datum_t * response_type_oid

newly allocated output buffer with response type OID

gnutls_datum_t * response

newly allocated output buffer with DER encoded response

DESCRIPTION

This function will extract the response type OID in and the response data from an OCSP response.

Normally the

response_type_oid is always "1.3.6.1.5.5.7.48.1.1" which means the

response should be decoded as a Basic OCSP Response, but technically other response types could be used.

This function is typically only useful when you want to extract the response type OID of an response for diagnostic purposes. Otherwise **gnutls_ocsp_resp_import()** will decode the basic OCSP response part and the caller need not worry about that aspect.

Since 3.7.0 *response_type_oid* ->size does not account for the terminating null byte.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>