

**NAME**

gnutls\_pkcs11\_copy\_pubkey - API function

**SYNOPSIS**

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_copy_pubkey(const char * token_url, gnutls_pubkey_t pubkey, const char * label,  
const gnutls_datum_t * cid, unsigned int key_usage, unsigned int flags);
```

**ARGUMENTS**

const char \* token\_url

A PKCS 11 URL specifying a token

gnutls\_pubkey\_t pubkey

The public key to copy

const char \* label

The name to be used for the stored data

const gnutls\_datum\_t \* cid

The CKA\_ID to set for the object -if NULL, the ID will be derived from the public key

unsigned int key\_usage

One of GNUTLS\_KEY\_\*

unsigned int flags

One of GNUTLS\_PKCS11\_OBJ\_FLAG\_\*

**DESCRIPTION**

This function will copy a public key object into a PKCS 11 token specified by a URL. Valid flags to mark the key: **GNUTLS\_PKCS11\_OBJ\_FLAG\_MARK\_TRUSTED**,

**GNUTLS\_PKCS11\_OBJ\_FLAG\_MARK\_PRIVATE**, **GNUTLS\_PKCS11\_OBJ\_FLAG\_MARK\_CA**,  
**GNUTLS\_PKCS11\_OBJ\_FLAG\_MARK\_ALWAYS\_AUTH**.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

3.4.6

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.   
Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium  
without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>