

NAME

gnutls_pkcs11_copy_x509_cert - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
int gnutls_pkcs11_copy_x509_cert(const char * token_url, gnutls_x509_cert_t crt, const char * label, unsigned int flags);
```

ARGUMENTS

const char * token_url

A PKCS **11** URL specifying a token

gnutls_x509_cert_t crt

A certificate

const char * label

A name to be used for the stored data

unsigned int flags

One of GNUTLS_PKCS11_OBJ_FLAG_*

DESCRIPTION

This function will copy a certificate into a PKCS **11** token specified by a URL. The certificate can be marked as trusted or not.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>