

NAME

gnutls_pkcs11_obj_set_pin_function - API function

SYNOPSIS

```
#include <gnutls/pkcs11.h>
```

```
void gnutls_pkcs11_obj_set_pin_function(gnutls_pkcs11_obj_t obj, gnutls_pin_callback_t fn, void * userdata);
```

ARGUMENTS

gnutls_pkcs11_obj_t obj
The object structure

gnutls_pin_callback_t fn
the callback

void * userdata
data associated with the callback

DESCRIPTION

This function will set a callback function to be used when required to access the object. This function overrides the global set using **gnutls_pkcs11_set_pin_function()**.

SINCE

3.1.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_pkcs11_obj_set_pin_function(3)

gnutls

gnutls_pkcs11_obj_set_pin_function(3)

<https://www.gnutls.org/manual/>