

**NAME**

gnutls\_pkcs12\_bag\_encrypt - API function

**SYNOPSIS**

```
#include <gnutls/pkcs12.h>
```

```
int gnutls_pkcs12_bag_encrypt(gnutls_pkcs12_bag_t bag, const char * pass, unsigned int flags);
```

**ARGUMENTS**

gnutls\_pkcs12\_bag\_t bag

The bag

const char \* pass

The password used for encryption, must be ASCII

unsigned int flags

should be one of **gnutls\_pkcs\_encrypt\_flags\_t** elements bitwise or'd

**DESCRIPTION**

This function will encrypt the given bag.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error code is returned.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>