

NAME

gnutls_pkcs7_get_signature_info - API function

SYNOPSIS

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_get_signature_info(gnutls_pkcs7_t pkcs7, unsigned idx,  
gnutls_pkcs7_signature_info_st * info);
```

ARGUMENTS

gnutls_pkcs7_t pkcs7
should contain a **gnutls_pkcs7_t** type

unsigned idx the index of the signature info to check

gnutls_pkcs7_signature_info_st * info
will contain the output signature

DESCRIPTION

This function will return information about the signature identified by *idx* in the provided PKCS 7 structure. The information should be deinitialized using **gnutls_pkcs7_signature_info_deinit()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.4.2

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/`

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>