

**NAME**

gnutls\_pkcs7\_set\_crl - API function

**SYNOPSIS**

```
#include <gnutls/pkcs7.h>
```

```
int gnutls_pkcs7_set_crl(gnutls_pkcs7_t pkcs7, gnutls_x509_crl_t crl);
```

**ARGUMENTS**

gnutls\_pkcs7\_t pkcs7  
The pkcs7 type

gnutls\_x509\_crl\_t crl  
the DER encoded crl to be added

**DESCRIPTION**

This function will add a parsed CRL to the PKCS7 or RFC2630 crl set.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>