

NAME

gnutls_privkey_import_x509 - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_privkey_import_x509(gnutls_privkey_t pkey, gnutls_x509_privkey_t key, unsigned int flags);
```

ARGUMENTS

gnutls_privkey_t pkey

The private key

gnutls_x509_privkey_t key

The private key to be imported

unsigned int flags

Flags for the import

DESCRIPTION

This function will import the given private key to the abstract **gnutls_privkey_t** type.

The **gnutls_x509_privkey_t** object must not be deallocated during the lifetime of this structure.

flags might be zero or one of **GNUTLS_PRIVKEY_IMPORT_AUTO_RELEASE** and **GNUTLS_PRIVKEY_IMPORT_COPY**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>