

## NAME

gnutls\_psk\_server\_get\_username - API function

## SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
const char * gnutls_psk_server_get_username(gnutls_session_t session);
```

## ARGUMENTS

gnutls\_session\_t session  
is a gnutls session

## DESCRIPTION

This should only be called in case of PSK authentication and in case of a server.

The returned pointer should be considered constant (do not free) and valid for the lifetime of the session.

This function will return **NULL** if the username has embedded NULL bytes. In that case, **gnutls\_psk\_server\_get\_username2()** should be used to retrieve the username.

## RETURNS

the username of the peer, or **NULL** in case of an error, or if the username has embedded NULLs.

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>