

NAME

gnutls_psk_set_server_credentials_file - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_psk_set_server_credentials_file(gnutls_psk_server_credentials_t res, const char * password_file);
```

ARGUMENTS

gnutls_psk_server_credentials_t res
is a **gnutls_psk_server_credentials_t** type.

const char * password_file
is the PSK password file (passwd.psk)

DESCRIPTION

This function sets the password file, in a **gnutls_psk_server_credentials_t** type. This password file holds usernames and keys and will be used for PSK authentication.

Each entry in the file consists of a username, followed by a colon (':') and a hex-encoded key. If the username contains a colon or any other special character, it can be hex-encoded preceded by a

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise an error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_psk_set_server_credentials_file(3)

gnutls

gnutls_psk_set_server_credentials_file(3)

<https://www.gnutls.org/manual/>