

NAME

gnutls_pubkey_encrypt_data - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_encrypt_data(gnutls_pubkey_t key, unsigned int flags, const gnutls_datum_t *  
plaintext, gnutls_datum_t * ciphertext);
```

ARGUMENTS

gnutls_pubkey_t key

Holds the public key

unsigned int flags

should be 0 for now

const gnutls_datum_t * plaintext

The data to be encrypted

gnutls_datum_t * ciphertext

contains the encrypted data

DESCRIPTION

This function will encrypt the given data, using the public key. On success the *ciphertext* will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>