

NAME

gnutls_pubkey_import_url - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_import_url(gnutls_pubkey_t key, const char * url, unsigned int flags);
```

ARGUMENTS

gnutls_pubkey_t key

A key of type **gnutls_pubkey_t**

const char * url

A PKCS 11 url

unsigned int flags

One of GNUTLS_PKCS11_OBJ_* flags

DESCRIPTION

This function will import a public key from the provided URL.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.1.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_pubkey_import_url(3)

gnutls

gnutls_pubkey_import_url(3)

<https://www.gnutls.org/manual/>