

**NAME**

gnutls\_pubkey\_import\_x509 - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_pubkey_import_x509(gnutls_pubkey_t key, gnutls_x509_cert_t crt, unsigned int flags);
```

**ARGUMENTS**

gnutls\_pubkey\_t key

The public key

gnutls\_x509\_cert\_t crt

The certificate to be imported

unsigned int flags

should be zero

**DESCRIPTION**

This function will import the given public key to the abstract **gnutls\_pubkey\_t** type.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

2.12.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>