

NAME

gnutls_pubkey_set_pin_function - API function

SYNOPSIS

```
#include <gnutls/abstract.h>
```

```
void gnutls_pubkey_set_pin_function(gnutls_pubkey_t key, gnutls_pin_callback_t fn, void * userdata);
```

ARGUMENTS

gnutls_pubkey_t key

A key of type **gnutls_pubkey_t**

gnutls_pin_callback_t fn

the callback

void * userdata

data associated with the callback

DESCRIPTION

This function will set a callback function to be used when required to access the object. This function overrides any other global PIN functions.

Note that this function must be called right after initialization to have effect.

SINCE

3.1.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_pubkey_set_pin_function(3)

gnutls

gnutls_pubkey_set_pin_function(3)

<https://www.gnutls.org/manual/>