

NAME

gnutls_record_rcv_seq - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
ssize_t gnutls_record_rcv_seq(gnutls_session_t session, void * data, size_t data_size, unsigned char * seq);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

void * data the buffer that the data will be read into

size_t data_size

the number of requested bytes

unsigned char * seq

is the packet's 64-bit sequence number. Should have space for 8 bytes.

DESCRIPTION

This function is the same as **gnutls_record_rcv()**, except that it returns in addition to data, the sequence number of the data. This is useful in DTLS where record packets might be received out-of-order. The returned 8-byte sequence number is an integer in big-endian format and should be treated as a unique message identification.

RETURNS

The number of bytes received and zero on EOF. A negative error code is returned in case of an error. The number of bytes received might be less than *data_size* .

SINCE

3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>