

NAME

gnutls_session_set_premaster - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_session_set_premaster(gnutls_session_t session, unsigned int entity, gnutls_protocol_t
version, gnutls_kx_algorithm_t kx, gnutls_cipher_algorithm_t cipher, gnutls_mac_algorithm_t mac,
gnutls_compression_method_t comp, const gnutls_datum_t * master, const gnutls_datum_t *
session_id);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

unsigned int entity

GNUTLS_SERVER or GNUTLS_CLIENT

gnutls_protocol_t version

the TLS protocol version

gnutls_kx_algorithm_t kx

the key exchange method

gnutls_cipher_algorithm_t cipher

the cipher

gnutls_mac_algorithm_t mac

the MAC algorithm

gnutls_compression_method_t comp

the compression method (ignored)

const gnutls_datum_t * master

the master key to use

const gnutls_datum_t * session_id

the session identifier

DESCRIPTION

This function sets the premaster secret in a session. This is a function intended for exceptional uses. Do not use this function unless you are implementing a legacy protocol. Use **gnutls_session_set_data()** instead.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise an error code is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>