

NAME

gnutls_session_ticket_enable_server - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_session_ticket_enable_server(gnutls_session_t session, const gnutls_datum_t * key);
```

ARGUMENTS

gnutls_session_t session

is a **gnutls_session_t** type.

const gnutls_datum_t * key

key to encrypt session parameters.

DESCRIPTION

Request that the server should attempt session resumption using session tickets, i.e., by delegating storage to the client.

key must be initialized using **gnutls_session_ticket_key_generate()**. To avoid leaking that key, use **gnutls_memset()** prior to releasing it.

The default ticket expiration time can be overridden using **gnutls_db_set_cache_expiration()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, or an error code.

SINCE

2.10.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>