

NAME

gnutls_srp_set_client_credentials - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_srp_set_client_credentials(gnutls_srp_client_credentials_t res, const char * username, const char * password);
```

ARGUMENTS

gnutls_srp_client_credentials_t res
is a **gnutls_srp_client_credentials_t** type.

const char * username
is the user's userid

const char * password
is the user's password

DESCRIPTION

This function sets the username and password, in a **gnutls_srp_client_credentials_t** type. Those will be used in SRP authentication. *username* should be an ASCII string or UTF-8 string. In case of a UTF-8 string it is recommended to be following the PRECIS framework for usernames (rfc8265). The password can be in ASCII format, or normalized using **gnutls_utf8_password_normalize()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, or an error code.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/`

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>