

## NAME

gnutls\_subject\_alt\_names\_get - API function

## SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_subject_alt_names_get(gnutls_subject_alt_names_t sans, unsigned int seq, unsigned int *  
san_type, gnutls_datum_t * san, gnutls_datum_t * othername_oid);
```

## ARGUMENTS

gnutls\_subject\_alt\_names\_t sans

The alternative names

unsigned int seq

The index of the name to get

unsigned int \* san\_type

Will hold the type of the name (of **gnutls\_subject\_alt\_names\_t**)

gnutls\_datum\_t \* san

The alternative name data (should be treated as constant)

gnutls\_datum\_t \* othername\_oid

The object identifier if *san\_type* is **GNUTLS\_SAN\_OTHERNAME** (should be treated as constant)

## DESCRIPTION

This function will return a specific alternative name as stored in the *sans* type. The returned values should be treated as constant and valid for the lifetime of *sans*.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned,

**GNUTLS\_E\_REQUESTED\_DATA\_NOT\_AVAILABLE** if the index is out of bounds, otherwise a negative error value.

## SINCE

3.3.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## **COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## **SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>