

gnutls_x509_crl_get_signature_algorithm(3) gnutls gnutls_x509_crl_get_signature_algorithm(3)

NAME

gnutls_x509_crl_get_signature_algorithm - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_get_signature_algorithm(gnutls_x509_crl_t crl);
```

ARGUMENTS

gnutls_x509_crl_t *crl*
should contain a **gnutls_x509_crl_t** type

DESCRIPTION

This function will return a value of the **gnutls_sign_algorithm_t** enumeration that is the signature algorithm.

Since 3.6.0 this function never returns a negative error code. Error cases and unknown/unsupported signature algorithms are mapped to **GNUTLS_SIGN_UNKNOWN**.

RETURNS

a **gnutls_sign_algorithm_t** value

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>