

NAME

gnutls_x509_crl_verify - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_verify(gnutls_x509_crl_t crl, const gnutls_x509_crt_t * trusted_cas, unsigned tcas_size, unsigned int flags, unsigned int * verify);
```

ARGUMENTS

gnutls_x509_crl_t *crl*

is the crl to be verified

const gnutls_x509_crt_t * *trusted_cas*

is a certificate list that is considered to be trusted one

unsigned *tcas_size*

holds the number of CA certificates in *CA_list*

unsigned int *flags*

Flags that may be used to change the verification algorithm. Use OR of the `gnutls_certificate_verify_flags` enumerations.

unsigned int * *verify*

will hold the crl verification output.

DESCRIPTION

This function will try to verify the given crl and return its verification status. See `gnutls_x509_crt_list_verify()` for a detailed description of return values. Note that since GnuTLS 3.1.4 this function includes the time checks.

Note that value in *verify* is set only when the return value of this function is success (i.e, failure to trust a CRL a certificate does not imply a negative return value).

Before GnuTLS 3.5.7 this function would return zero or a positive number on success.

RETURNS

On success, `GNUTLS_E_SUCCESS` (0), otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>