

NAME

gnutls_x509_crq_import - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_import(gnutls_x509_crq_t crq, const gnutls_datum_t * data,  
gnutls_x509_crq_fmt_t format);
```

ARGUMENTS

gnutls_x509_crq_t crq

The data to store the parsed certificate request.

const gnutls_datum_t * data

The DER or PEM encoded certificate.

gnutls_x509_crq_fmt_t format

One of DER or PEM

DESCRIPTION

This function will convert the given DER or PEM encoded certificate request to a **gnutls_x509_crq_t** type. The output will be stored in *crq*.

If the Certificate is PEM encoded it should have a header of "NEW CERTIFICATE REQUEST".

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/`

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>