

NAME

gnutls_x509_crt_get_fingerprint - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crt_get_fingerprint(gnutls_x509_crt_t cert, gnutls_digest_algorithm_t algo, void * buf,  
size_t * buf_size);
```

ARGUMENTS

gnutls_x509_crt_t *cert*

should contain a **gnutls_x509_crt_t** type

gnutls_digest_algorithm_t *algo*

is a digest algorithm

void * *buf* a pointer to a structure to hold the fingerprint (may be null)

size_t * *buf_size*

initially holds the size of *buf*

DESCRIPTION

This function will calculate and copy the certificate's fingerprint in the provided buffer. The fingerprint is a hash of the DER-encoded data of the certificate.

If the buffer is null then only the size will be filled.

RETURNS

GNUTLS_E_SHORT_MEMORY_BUFFER if the provided buffer is not long enough, and in that case the **buf_size* will be updated with the required size. On success 0 is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>