

NAME

gnutls_x509_cert_get_key_usage - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_get_key_usage(gnutls_x509_cert_t cert, unsigned int * key_usage, unsigned int * critical);
```

ARGUMENTS

gnutls_x509_cert_t cert

should contain a **gnutls_x509_cert_t** type

unsigned int * key_usage

where the key usage bits will be stored

unsigned int * critical

will be non-zero if the extension is marked as critical

DESCRIPTION

This function will return certificate's key usage, by reading the keyUsage X.509 extension (2.5.29.15).

The key usage value will ORed values of the: **GNUTLS_KEY_DIGITAL_SIGNATURE**, **GNUTLS_KEY_NON_REPUDIATION**, **GNUTLS_KEY_KEY_ENCIPHERMENT**, **GNUTLS_KEY_DATA_ENCIPHERMENT**, **GNUTLS_KEY_KEY_AGREEMENT**, **GNUTLS_KEY_KEY_CERT_SIGN**, **GNUTLS_KEY_CRL_SIGN**, **GNUTLS_KEY_ENCIPHER_ONLY**, **GNUTLS_KEY_DECIPHER_ONLY**.

RETURNS

zero on success, or a negative error code in case of parsing error. If the certificate does not contain the keyUsage extension **GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE** will be returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>