

gnutls_x509_cert_set_authority_key_id(3) gnutls gnutls_x509_cert_set_authority_key_id(3)

NAME

gnutls_x509_cert_set_authority_key_id - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_authority_key_id(gnutls_x509_cert_t cert, const void * id, size_t id_size);
```

ARGUMENTS

gnutls_x509_cert_t cert
a certificate of type **gnutls_x509_cert_t**

const void * id
The key ID

size_t id_size Holds the size of the key ID field.

DESCRIPTION

This function will set the X.509 certificate's authority key ID extension. Only the keyIdentifier field can be set with this function.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>