

**NAME**

gnutls\_x509\_cert\_set\_crl\_dist\_points - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_crl_dist_points(gnutls_x509_cert_t crt, gnutls_x509_subject_alt_name_t type,  
const void * data_string, unsigned int reason_flags);
```

**ARGUMENTS**

gnutls\_x509\_cert\_t crt

a certificate of type **gnutls\_x509\_cert\_t**

gnutls\_x509\_subject\_alt\_name\_t type

is one of the gnutls\_x509\_subject\_alt\_name\_t enumerations

const void \* data\_string

The data to be set

unsigned int reason\_flags

revocation reasons

**DESCRIPTION**

This function will set the CRL distribution points certificate extension.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>