

gnutls_x509_cert_set_crq_extension_by_oid(3) gnutls gnutls_x509_cert_set_crq_extension_by_oid(3)

NAME

gnutls_x509_cert_set_crq_extension_by_oid - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_crq_extension_by_oid(gnutls_x509_cert_t crt, gnutls_x509_crq_t crq, const char * oid, unsigned flags);
```

ARGUMENTS

gnutls_x509_cert_t crt
a certificate of type **gnutls_x509_cert_t**

gnutls_x509_crq_t crq
holds a certificate request

const char * oid
the object identifier of the OID to copy

unsigned flags
should be zero

DESCRIPTION

This function will set the extension specify by *oid* from the given request to the certificate.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.5.1

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

gnutls_x509_cert_set_crq_extension_by_oid(3) gnutls gnutls_x509_cert_set_crq_extension_by_oid(3)

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>