

NAME

gnutls_x509_cert_set_proxy_dn - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_proxy_dn(gnutls_x509_cert_t crt, gnutls_x509_cert_t eecrt, unsigned int raw_flag, const void * name, unsigned int sizeof_name);
```

ARGUMENTS

gnutls_x509_cert_t *crt*

a gnutls_x509_cert_t type with the new proxy cert

gnutls_x509_cert_t *eecrt*

the end entity certificate that will be issuing the proxy

unsigned int *raw_flag*

must be 0, or 1 if the CN is DER encoded

const void * *name*

a pointer to the CN name, may be NULL (but MUST then be added later)

unsigned int *sizeof_name*

holds the size of *name*

DESCRIPTION

This function will set the subject in *crt* to the end entity's *eecrt* subject name, and add a single Common Name component *name* of size *sizeof_name*. This corresponds to the required proxy certificate naming style. Note that if *name* is **NULL**, you MUST set it later by using **gnutls_x509_cert_set_dn_by_oid()** or similar.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>