

gnutls\_x509\_ext\_export\_inhibit\_anypolicy(3) gnutls gnutls\_x509\_ext\_export\_inhibit\_anypolicy(3)

## NAME

gnutls\_x509\_ext\_export\_inhibit\_anypolicy - API function

## SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_inhibit_anypolicy(unsigned int skipcerts, gnutls_datum_t * ext);
```

## ARGUMENTS

unsigned int *skipcerts*

number of certificates after which anypolicy is no longer acceptable.

gnutls\_datum\_t \* *ext*

The DER-encoded extension data; must be freed using **gnutls\_free()**.

## DESCRIPTION

This function will convert the *skipcerts* value to a DER encoded Inhibit AnyPolicy PKIX extension. The *ext* data will be allocated using **gnutls\_malloc()**.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

## SINCE

3.6.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>