

gnutls_x509_ext_export_subject_alt_names(3) gnutls gnutls_x509_ext_export_subject_alt_names(3)

NAME

gnutls_x509_ext_export_subject_alt_names - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_subject_alt_names(gnutls_subject_alt_names_t sans, gnutls_datum_t *  
ext);
```

ARGUMENTS

gnutls_subject_alt_names_t sans
The alternative names

gnutls_datum_t * ext
The DER-encoded extension data; must be freed using **gnutls_free()**.

DESCRIPTION

This function will convert the provided alternative names structure to a DER-encoded SubjectAltName PKIX extension. The output data in *ext* will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_x509_ext_export_subject_alt_names(3) gnutls gnutls_x509_ext_export_subject_alt_names(3)

<https://www.gnutls.org/manual/>