

NAME

gnutls_x509_policies_get - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_policies_get(gnutls_x509_policies_t policies, unsigned int seq, struct  
gnutls_x509_policy_st * policy);
```

ARGUMENTS

gnutls_x509_policies_t *policies*

The policies

unsigned int *seq*

The index of the name to get

struct gnutls_x509_policy_st * *policy*

Will hold the policy

DESCRIPTION

This function will return a specific policy as stored in the *policies* type. The returned values should be treated as constant and valid for the lifetime of *policies* .

The any policy OID is available as the **GNUTLS_X509_OID_POLICY_ANY** macro.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned,

GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE if the index is out of bounds, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>