

NAME

gnutls_x509_privkey_get_spki - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_privkey_get_spki(gnutls_x509_privkey_t key, gnutls_x509_spki_t spki, unsigned int flags);
```

ARGUMENTS

gnutls_x509_privkey_t key

should contain a **gnutls_x509_privkey_t** type

gnutls_x509_spki_t spki

a SubjectPublicKeyInfo structure of type **gnutls_x509_spki_t**

unsigned int flags

must be zero

DESCRIPTION

This function will return the public key information of a private key. The provided *spki* must be initialized.

RETURNS

Zero on success, or a negative error code on error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_x509_privkey_get_spki(3)

gnutls

gnutls_x509_privkey_get_spki(3)

<https://www.gnutls.org/manual/>