

**NAME**

gnutls\_x509\_rdn\_get2 - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_rdn_get2(const gnutls_datum_t * idn, gnutls_datum_t * str, unsigned flags);
```

**ARGUMENTS**

const gnutls\_datum\_t \* idn

should contain a DER encoded RDN sequence

gnutls\_datum\_t \* str

a datum that will hold the name

unsigned flags

zero of **GNUTLS\_X509\_DN\_FLAG\_COMPAT**

**DESCRIPTION**

This function will return the name of the given RDN sequence. The name will be in the form "C=xxxx,O=yyyy,CN=zzzz" as described in RFC4514.

When the flag **GNUTLS\_X509\_DN\_FLAG\_COMPAT** is specified, the output format will match the format output by previous to 3.5.6 versions of GnuTLS which was not not fully RFC4514-compliant.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, or **GNUTLS\_E\_SHORT\_MEMORY\_BUFFER** is returned and \* *buf\_size* is updated if the provided buffer is not long enough, otherwise a negative error value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>