

## NAME

gnutls\_x509\_spki\_set\_rsa\_pss\_params - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
void gnutls_x509_spki_set_rsa_pss_params(gnutls_x509_spki_t spki, gnutls_digest_algorithm_t dig,  
unsigned int salt_size);
```

## ARGUMENTS

gnutls\_x509\_spki\_t *spki*  
the SubjectPublicKeyInfo structure

gnutls\_digest\_algorithm\_t *dig*  
a digest algorithm of type **gnutls\_digest\_algorithm\_t**

unsigned int *salt\_size*  
the size of salt string

## DESCRIPTION

This function will set the public key parameters for an RSA-PSS algorithm, in the SubjectPublicKeyInfo structure.

## SINCE

3.6.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls\_x509\_spki\_set\_rsa\_pss\_params(3)

gnutls

gnutls\_x509\_spki\_set\_rsa\_pss\_params(3)

<https://www.gnutls.org/manual/>