

NAME

gnutls_x509_tlsfeatures_get - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_tlsfeatures_get(gnutls_x509_tlsfeatures_t f, unsigned idx, unsigned int *feature);
```

ARGUMENTS

gnutls_x509_tlsfeatures_t f

The TLS features

unsigned idx The index of the feature to get

unsigned int * feature

If the function succeeds, the feature will be stored in this variable

DESCRIPTION

This function will get a feature from the X.509 TLS features extension structure.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.5.1

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_x509_tlsfeatures_get(3)

gnutls

gnutls_x509_tlsfeatures_get(3)

<https://www.gnutls.org/manual/>