

**NAME**

gnutls\_x509\_trust\_list\_deinit - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
void gnutls_x509_trust_list_deinit(gnutls_x509_trust_list_t list, unsigned int all);
```

**ARGUMENTS**

gnutls\_x509\_trust\_list\_t list

The list to be deinitialized

unsigned int all

if non-zero it will deinitialize all the certificates and CRLs contained in the structure.

**DESCRIPTION**

This function will deinitialize a trust list. Note that the *all* flag should be typically non-zero unless you have specified your certificates using **gnutls\_x509\_trust\_list\_add\_cas()** and you want to prevent them from being deinitialized by this function.

**SINCE**

3.0.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>