

NAME

gsasl_callback_hook_set - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
void gsasl_callback_hook_set(Gsasl * ctx, void * hook);
```

ARGUMENTS

Gsasl * ctx libgsasl handle.

void * hook opaque pointer to application specific data.

DESCRIPTION

Store application specific data in the libgsasl handle.

The application data can be later (for instance, inside a callback) be retrieved by calling **gsasl_callback_hook_get()**. This is normally used by the application to maintain a global state between the main program and callbacks.

SINCE

0.2.0

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

```
info gsasl
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>